

Get Gift Card



Feature: Gift Cards



Editions: Cloud, Corporate*

The `giftcard` endpoint can be queried to retrieve gift card information.

To enable various use cases – especially access by trusted and non-trusted API clients – several permissions are used to refine how gift card results are returned. The following permissions are the most common:

- `FindGiftCardByCode` – the client can query for a gift card by supplying the code. This is the most common use case.
- `UseExternalGiftCardCodes` – the client can view external codes; this use case is for third party integrations that manage their own gift card codes, e.g. an ecommerce system.
- `UsePhysicalGiftCardCodes` – the client can view physical codes.

There are additional permissions that can be used, but have limited use cases. These permissions should be used when necessary and for high-trust clients – e.g. server environments that you can secure – as they can expose sensitive gift card details:

- `ListGiftCards` – the client query gift cards without supplying a code value. This is a limited case that should be only used for high-trust clients.
- `ViewUnmaskedGiftCardCodes` – the client can view electronic (digital) codes. Again, this is a limited case that should only be used for high-trust clients.
- `UseCryptoGiftCardCodes` – the client can view electronic (digital) codes, either in masked form (recommended) or unmasked form (as specified above). This is a limited use case.
- `UseShortPersonalGiftCardCodes` – reserved for future use.

Examples

Get Card by Code

Return a gift card that matches a specific code:



```
query MyQuery {
  giftcard(code: "G59220000045", codeType: PHYSICAL) {
    limitedByPermission
    results {
      id
      memberId
      balance
      codes {
        id
        codeType
        code
        expiresOn
        isMasked
      }
    }
  }
}
```

Note:

- While the `codeType` parameter is optional, it is recommended.
 - Gift card codes must be unique within a code type, so that they uniquely identify a gift card.
 - It is recommended to keep codes unique across all code types, but it is not required.
 - If codes are *not* unique across all code types, the `codeType` parameter is required to resolve the correct gift card.
- This type of request requires `FindGiftCardByCode` permission.

Get Card by ID

Return a gift card that matches the specified internal ID:

```
query MyQuery {
  giftcard(id: "302") {
    limitedByPermission
    results {
      id
      memberId
      balance
      codes {
        id
        codeType
      }
    }
  }
}
```



```
      code
      expiresOn
      isMasked
    }
  }
}
```

This type of query should only be used by trusted clients, and requires `ListGiftCards` permission.

List Cards for Member

Return the list of gift cards that are owned by a specific member:

```
query MyQuery {
  giftcard(memberId: "C0000000113") {
    limitedByPermission
    results {
      id
      memberId
      balance
      codes {
        id
        codeType
        code
        expiresOn
        isMasked
      }
    }
  }
}
```

This type of query should only be used by trusted clients, and requires `ListGiftCards` permission.